

户外 三相 高压计量箱
OUTDOOR SINGLE-PHASE HIGH-VOLTAGE METERING BOX

技术参数 Technical data

- 产品性能符合标准 GB17201
The voltage transformers are in accordance with GB17201
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 环境温度: $-25^{\circ}\text{C}\sim+40^{\circ}\text{C}$
Ambient temperature $-25^{\circ}\text{C}\sim+40^{\circ}\text{C}$
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 污秽等级IV级
Pollution class IV



额定电流比 Rated current ratio(A)	准确级组合 Class combination	准确级及额定输出 $\text{COS}\Phi=0.8$ Accuracy class and rated output(VA)		额定短时热电流 Rated short-time thermal current(kA)	额定动稳定电流 Rated dynamic current(kA)
		0.2(S)	0.5		
5/5-75/5	0.2(S) 0.5	10或15	10或15	100lin	250lin
100/5-200/5				150lin	375lin
300/5				31.5	80
400/5-600/5				63	130
额定电压比 Rated voltage ratio(A)	准确级组合 Class combination	准确级及额定输出 $\text{COS}\Phi=0.8$ Accuracy class and rated output(VA)		二次热极限输出 Limiting thermal output of secondary winding (kA)	
		0.2	0.5	350	
33/0.1	0.2	30	60		
35/0.1	0.5				

外形及安装尺寸 Overall dimension drawing

