

户内 三相 环氧树脂浇注式
INDOOR THREE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1207和IEC60044-2
The voltage transformers are in accordance with GB1207 and IEC60044-2 standards
- 额定绝缘水平 12/42/75、7.2/32/60kV
Rated insulation level 12/42/75、7.2/32/60kV
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz



额定电压比 Rated voltage ratio (V)	准确级及三相额定二次输出(VA) Accuracy class Three-phase rated secondary output	极限输出 Max.output (VA)	额定绝缘水平 Rated insulation level(kV)	接线图 Wiring diagram
3000/100	0.2-- $30 \times \sqrt{3}$ 0.5-- $90 \times \sqrt{3}$ 1-- $250 \times \sqrt{3}$	$600 \times \sqrt{3}$	3.6/23/40	图1 Figure 1
6000/100			7.2/32/60	
10000/100			12/42/75	
3000/100/100	0.2/0.2-- $20 \times \sqrt{3} / 20 \times \sqrt{3}$ 0.2/0.5-- $20 \times \sqrt{3} / 20 \times \sqrt{3}$ 0.5/0.5-- $45 \times \sqrt{3} / 45 \times \sqrt{3}$	$500 \times \sqrt{3}$ $500 \times \sqrt{3}$	3.6/23/40	图2 Figure 2
6000/100/100			7.2/32/60	
10000/100/100			12/42/75	
10000/100/220	0.2/3-- $30 \times \sqrt{3} / 300$ 0.5/3-- $90 \times \sqrt{3} / 300$	$600 \times \sqrt{3} / 1000$	12/42/75	

注：一次端子电缆连接形式：JSZV12A-3、6、10R一次端子与美式200A大口径肘型插头配套使用。

Note: The first wiring point connection mode: JSZV12A-3、6、10R first wiring point and 200A American type heavy-calibre elbow plug cooperate.

外形及安装尺寸 Overall dimension drawing

