

# JSZV16-24R

型电压互感器 VOLTAGE TRANSFORMER



上海互凌

Shanghai Huling Electric Co., Ltd.

户内 三相 环氧树脂浇注式

INDOOR THREE-PHASE EPOXY RESIN CASTING TYPE

## 技术参数 Technical data

- 产品性能符合标准 GB1207和IEC60044-2  
The current transformers are in accordance with GB1207 and IEC60044-2 standards
- 额定绝缘水平 24/65/125kV  
Rated insulation level 24/65/125kV
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz



| 型号<br>Type | 额定电压比(kV)<br>Rated voltage ratio | 准确级组合<br>Class combination | 准确级及额定输出(VA) $\cos\phi=0.8$<br>Accuracy class and rated output |     |     | 二次热极限输出(VA)<br>Limiting thermal output of secondary winding | 重量(kg)<br>Weight |
|------------|----------------------------------|----------------------------|----------------------------------------------------------------|-----|-----|-------------------------------------------------------------|------------------|
|            |                                  |                            | 0.2                                                            | 0.5 | 1.0 |                                                             |                  |
| JSZV16-24R | 20/0.1                           | 0.2、0.5、1.0                | 40                                                             | 100 | 150 | 2 × 400                                                     | 70               |
| JSZV16-24R | 20/0.1/0.22                      | 0.2、0.5、1.0                | 30                                                             | 60  | 100 | 电源最大输出 2 × 400                                              |                  |

注： 1、如用户要求的参数超出上表范围，可与我公司协商后确定。

Note: 1. If user's data go beyond the above-mentioned scope, they may be subject to an agreement between manufacturer and purchaser.

2、配用熔断器型号为XRNP□-12、7.2型，0.2、0.5A,50kA

2. The fusible cutout's type: XRNP□-12、7.2, 0.2、0.5A,50kA.

3、配用肘形电缆头为20kV电压等级，美式200A。

3. The voltage class of the attached cable head is 20kV、American 200A.

## 外形及安装尺寸 Overall dimension drawing

