



户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current(kA)	动稳定电流 Rated dynamic current(kA)
		0.2S	0.5S	0.2	0.5	10P10		
5-200	0.2(S)/10P10	10	10	10	15	15	90lin	200lin
300、400							24.5	44
500	32						80	
600	32						80	
800-1000	0.5(S)/10P15						15*	

注: 代替LAJ-10时的表中参数, 测量级为带*数据, 保护级为10P15。

Note: Parameters in the table instead of LAJ-10: The measurement grade is the data marked with*, the protection grade is 10P15.

外形及安装尺寸 Overall dimension drawing

