

LCZ-35

型电流互感器 CURRENT TRANSFORMER

户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)
		0.2	0.5	10P10	10P15	10P20		
15	0.2(S)/0.2(S) 0.2(S)/0.5(S) 0.5(S)/0.5(S) 0.2(S)/10P 10P/10P	30	50	50	40	30	2	5
20							2.6	6.5
30							3.6	9
40							4.6	11.5
50							5.8	14.5
75							9.3	23
100							12.6	31.5
150							18	45
200							25	62.5
300							36	90
400							45	90
500							54	100
600							63	100
800							80	130
1000							100	130
1200								

外形及安装尺寸 Overall dimension drawing

