

# LDBJ9-40.5

型电流互感器 CURRENT TRANSFORMER



## 上海互凌

Shanghai Huling Electric Co.,Ltd.

### 户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV  
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A  
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C  
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				一秒热稳定电流 1s thermal current (kA)	额定动稳定电流 Rated dynamic current (kA)
		0.2S	0.2	0.5	5P10		
20-300	0.2(S)/5P10 0.5(S)/5P10	10	10	20	20	150lin	375lin
400					40	54	120
500					40	63	130
600-800		15	30	50	50	80	130
1000-1500					50	100	160
2000-3000							

#### 外形及安装尺寸 Overall dimension drawing

