

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: $-5^{\circ}\text{C}\sim+40^{\circ}\text{C}$
Ambient temperature $-5^{\circ}\text{C}\sim+40^{\circ}\text{C}$



额定一次电流 (A)	准确级组合及相应额定输出				额定短时热电流 (KA)	额定动稳定电流 (KA)
	0.2/10P10	0.5/10P10	0.2/0.5	10P10/10P10		
5~300	10/30	20/30	10/20	15/15	150I _{tn}	375I _{tn}
400	10/40	15/40	10/15	20/20	54	120
500	10/40	15/40	10/15	20/20	63	130
600	10/50	30/50	10/30	30/30		
800	15/50	30/50	15/30	30/30		
1000~2000	20/50	50/50	20/50	40/40	80	

外形及安装尺寸 Overall dimension drawing



