

LDJ1-35H/300

型电流互感器 CURRENT TRANSFORMER



上海互凌

Shanghai Huling Electric Co.,Ltd.

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)						一秒热稳定电流 1s thermal current (kA)	额定动稳定电流 Rated dynamic current (kA)			
		0.2S	0.5S	0.2	0.5	5P10	5P15			5P20		
5-300	0.2(S)/0.2(S) 0.2(S)/0.5(S) 0.5(S)/0.5(S) 5P10/5P10 5P15/5P15	10		10	20	30	40	20	15	10	150lin	375lin
400									15	10	54	120
500									15	10	63	130
600-800									15	10	63	130
1000-1600									15	10	80	130
2000	15	10	100	160								
5-300	0.2(S)/5P 0.5(S)/5P	10		10	15	30	40	30	15	15	150lin	375lin
400									15	15	54	120
500									15	15	63	130
600-800									15	15	63	130
1000-1600									15	15	80	130
2000	15	15	100	160								

外形及安装尺寸 Overall dimension drawing

