

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定电压：0.66kV
Rated voltage 0.66kV
- 额定二次电流：5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度：-5℃~+40℃
Ambient temperature -5℃~+40℃



| 额定电流比 Rated Current ratio (A) | 额定输出 Rated output(VA) | | |
|-------------------------------------|-----------------------|--------|-------|
| | 0.5 级 | 0.5S 级 | 0.2 级 |
| 5/5 | 5 | 5 | 5 |
| 10/5 | 5 | 5 | 5 |
| 15/5 | 5 | 5 | 5 |
| 20/5 | 5 | 5 | 5 |
| 30/5 | 5 | 5 | 5 |
| 40/5 | 5 | 5 | 5 |
| 50/5 | 5 | 5 | 5 |
| 75/5 | 5 | 5 | 5 |
| 100/5 | 5 | 5 | 5 |
| 150/5 | 5 | 5 | 5 |
| 200/5 | 5 | 5 | 5 |
| 250/5 | 5 | 5 | 5 |
| 300/5 | 5 | 5 | 5 |

外形及安装尺寸 Overall dimension drawing

