

LZW2-35

型户外电流互感器 OUTDOOR CURRENT TRANSFORMER



上海互凌

Shanghai Huling Electric Co., Ltd.

户外 单相 环氧树脂浇注式 OUTDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -25°C~+40°C
Ambient temperature -25°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)			一秒短时热电流 1s short-time thermal current(kA)	动稳定电流 Rated dynamic current (kA)
		0.2(S)	0.5	5P20		
10-100	0.2S 0.5 10P10	15	15	15	200lin	500lin
150-200					37.8	94.5
300-400					54	110
500-600			30	20	68.4	136
800-1000					95.5	190
1200-2000					140	200

外形及安装尺寸 Overall dimension drawing

