

◆型号含义 Type description

L ZW32 - 10 G2

第二次改型设计
No.2 improvement type
额定电压 (kV)
Rated voltage(kV)
真空断路器型号
Vacuum breaker type
电流互感器
Current transformer



◆技术参数 Technical date

产品型号 Type	额定电流比 Rated transformation ratio(A)	级次组合 Accuracy Classes combination	准确级及额定输出 (VA) Accuracy class and rated output $\cos\phi=0.8$				一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current(kA)	
			0.2	0.5	1	10P10			
LZW32-10G2	50/5	0.2/10P 0.5/10P 10/10P	10	10	15	20	20	9	22.5
	75/5							13.5	33.8
	100/5							18	45
	150/5							27	67.5
	200/5							36	90
	300/5							36	90
	400/5							40	100
	600/5							48	120
	630/5							48	120
	50-75-100/5							9	22.5
	75-100-150/5							13.5	33.8
	100-150-200/5							18	45
	150-200-300/5							27	67.5
	200-300-400/5							36	90
	200-400-600/5							48	120
	200-400-630/5							48	120

注：可根据用户要求制作多变比或特殊规格，多变比互感器在使用时只能使用其中一个变比，几个变比不能同时使用。

Note: Consumer such as have the special requirement and was negotiated by both parties cirtainty, the current transformer can but using one of the transformation ratios, and that can't using several transformation ratios at the same time.

◆外形及安装尺寸 Overall dimension drawing

