



户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				短时热电流 Short-time thermal current(kA/S)	动稳定电流 Rated dynamic current (kA)
		0.2S	0.2	0.5	10P10		
50	0.2(S)/10P10 0.5(S)/10P10	15	15	30	30	8/2	20
75						12/2	30
100						16/2	40
150						20/2	50
200						20/4	50
300						31.5/4	80
400						40/4	100
500						63	130
600						72	
750						80	
800							
1000							
1200							
1500							
2000							

外形及安装尺寸 Overall dimension drawing

