

户内 单相 环氧树脂浇注式
INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 24/65/125kV
Rated insulation level 24/65/125kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)
		0.2(S)	0.5(S)	10P10	10P15		
20-150	0.2(S)/0.2 0.2(S)/0.5 0.2(S)/10P10 0.5(S)/10P10 0.2(S)/10P15 0.5(S)/10P15	10	10	20	15	150lin	375lin
200						31.5	80
300-500						45	112.5
600、800		10	15	30	20	63	130
1000、1200						80	160
1500-2500		20	30	30	20	100	160

外形及安装尺寸 Overall dimension drawing

