

LZZBJ18-10/185h/2

型电流互感器 CURRENT TRANSFORMER



上海互凌

Shanghai Huling Electric Co.,Ltd.

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current(kA)	
		0.2S	0.5S	0.2	0.5	(5)10P10			(5)10P15
10-40	0.2S/10P	10		10	15	20	15	200lin	500lin
50-100								250lin	625lin
150-300	45							100	
400、500	63							150	
600-1000	80							160	
1200-1600	100							250	
2000-4000	0.5/10P	15	20	30			140	350	

外形及安装尺寸 Overall dimension drawing

