

## 户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

### 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV  
Rated insulation level 12/42/75kV
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 额定二次电流：5A或1A  
Rated secondary current 5A or 1A
- 环境温度：-5℃~+40℃  
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current (kA)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)				表面爬电距离 (mm)	重量(kg)
				0.2,0.2S	0.5,0.5S	10P10	10P15		
5	0.75	1.8							
10	1.5	3.75							
15	2	5							
20,25	3	7.5							
30	5	12.5							
40	6.3	15.8							
50,60	8	20							
75	12.5	31	0.2S/10P						
100	15	37.5	0.2/10P						
150	30	75	0.5/10P						
200,250			0.5S/10P						
300	45	112.5	0.2S/0.2	10	10	15	15	245	21/23
400									
500									
600	63	130	0.2S/0.5						
750,800									
1000									
1200,1250	80	160	0.2/0.5						
1500									
2000									
2500									
3000									
3150									

### 外形及安装尺寸 Overall dimension drawing

