



### 户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV  
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A  
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度: -5℃~+40℃  
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current(kA)	备注 Notes
		0.2S 0.5S	0.2	0.5	10P10	10P15			
5-150	0.2S/10P15 0.5S/10P15 0.2/10P15 0.5/10P15 10P10/10P10	10	10	15	15	20	150lin	375lin	两绕组 Two windings
200							36	80	
300-800							45	100	
1000-1500							63	130	
2000-3150							80	160	
5-150	0.2S/0.2/10P15 0.2S/0.5/10P15 0.2/0.5/10P15 0.5/0.5/10P15	10	10	15	15	15	150lin	375lin	三绕组 Three windings
200							36	80	
300-800							45	100	
1000-1500							63	130	
2000-3150							80	160	

#### 外形及安装尺寸 Overall dimension drawing

