



户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)			一秒热稳定电流 1s thermal current(kA)	动稳定电流 Rated dynamic current(kA)
		0.2S	0.2(0.5)	10P		
5	0.2S/10P10 0.2S/10P15 0.2/10P10 0.2/10P15 0.5/10P10 0.5/10P15	10	10	15*、20	0.5	1.25
10					1	2.5
15					1.5	3.75
20					3	7.5
25					3.75	9.3
30					4.5	11.2
40					6	15
50					7.5	18.7
75					10	25
100					15	37.5
150					22.5	56
200					31.5	80
300					45	112.5
400			10*、15		63	130
500					80	110
600			15*、30			
800						
1000						
1200						

注: 表中带*数据为常规产品时的参数。

Note: In the table, the data marked with*are the parameters of general products.

外形及安装尺寸 Overall dimension drawing

