

户内 单相 环氧树脂浇注式
INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)						一秒热稳定电流 1s thermal current (kA)	动稳定电流 Rated dynamic current(kA)
		0.2S	0.2	0.5	(5)10P10	(5)10P15	(5)10P20		
20-100	0.2(S)/10P 0.5/10P	10	10	10	10*、30	15*、20	15*、10	150lin	375lin
150、200								31.5	80
300、400	0.2(S)/0.2/5P 0.2(S)/0.5/5P		10	15	15*、30	20	15	45	112.5
500	0.2(S)/0.5/5P20 0.2(S)/5P10/10P15 0.5/5P10/10P20							15*、20	63
600-800			15	20					80
1000-1250									

注: 表中带*数据为级次组合0.2/5P10/10P15和0.5/5P10/10P20时的参数。
The data marked with* in the table are parameters for class combination 0.2/5P10/10P15 and 0.5/5P10/10P20.

外形及安装尺寸 Overall dimension drawing

