



户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: $-5^{\circ}\text{C}\sim+40^{\circ}\text{C}$
Ambient temperature $-5^{\circ}\text{C}\sim+40^{\circ}\text{C}$



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					一秒热稳定电流 1s thermal current(kA)	动稳定电流 Rated dynamic current(kA)
		0.2S	0.2	0.5	10P10	10P15		
5	0.2(S)/10P10 0.2(S)/10P15 0.5/10P10 0.5/10P15	10	10	15*、20	20	20	0.5	1.25
10							1	2.5
15							1.5	3.75
20							3	7.5
25							3.75	9.3
30							4.5	11.2
40							6	15
50							7.5	18.7
75							10	25
100							21	52.5
150							31.5	80
200				20	30	30	45	112.5
300							63	130
400							80	160
500							100	160
600								
800								
1000								
1200								
1500-3000				30	60	30		

注: 表中带*数据为0.5级/10P15时的参数。

The data marked with*in the table are parameters for class combination 0.5 and 10P15.

外形及安装尺寸 Overall dimension drawing

