



户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)			短时热电流 Short-time thermal current(kA/S)	额定动稳定电流 Rated dynamic current (kA)
		0.2	0.5	10P20		
20-100	0.2/0.2 0.2/0.5	10	15	15	200lin	500lin
150-200					31.5	
300-500	0.5/0.5	15	30	20	31.5/2	80
600-1250	0.2/5P20 0.5/5P20				31.5/4	
1500-2000	0.25/0.5/10P20	20	40	30	40/4	125
2500		20	40	20		

外形及安装尺寸 Overall dimension drawing

