

# LZZBW-35B(GY)

型户外电流互感器 OUTDOOR CURRENT TRANSFORMER



上海互凌

Shanghai Huling Electric Co.,Ltd.

户外 单相 环氧树脂浇注式

OUTDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

## 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 40.5/95/185kV  
Rated insulation level 40.5/95/185kV
- 额定二次电流: 5A或1A  
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度: -25℃~+40℃  
Ambient temperature -25℃~+40℃



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)			短时热稳定电流 short-time thermal current (kA)	动稳定电流 Rated dynamic current (kA)
		0.2(S)	0.5	5P20		
20-100	0.2(S)/5P20/5P20 0.5/5P20/5P20	10	15	15	150lin	375lin
150-200					31.5	
300-500					31.5/2	
600-1200		15	30	20	31.5/4	80
1500-2000		20	40	30	40/4	

## 外形及安装尺寸 Overall dimension drawing

