

# LZZJ-10Q

型电流互感器 CURRENT TRANSFORMER



## 上海互凌

Shanghai Huling Electric Co., Ltd.

### 户内 单相 环氧树脂浇注式 INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定绝缘水平 12/42/75kV  
Rated insulation level 12/42/75kV
- 额定二次电流: 5A或1A  
Rated secondary current 5A or 1A
- 额定频率50Hz或60Hz  
Rated frequency 50Hz or 60Hz
- 环境温度: -5°C~+40°C  
Ambient temperature -5°C~+40°C



额定一次电流 Rated primary current(A)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)			一秒热稳定电流 1s thermal current(kA)	动稳定电流 Rated dynamic current(kA)
		0.2S(0.2)	0.5S(0.5)	10P10		
5	0.2S/10P10	10	10	15	0.75	1.87
10					1.5	3.75
15					2.25	5.6
20					3	7.5
25					3.75	9.4
30					4.5	11.3
40					6	15
50					7.5	18.8
75					11.3	28.1
100					15	37.5
150	0.2/10P10	15	20	22.5	56.3	
200				30	75	
300				45	80	
400				63	100	
500	0.5/10P10	15	20	63	100	
600				80	130	
800				100	130	
1000				120	130	
1200				150	130	
1600				1600	130	

#### 外形及安装尺寸 Overall dimension drawing

