



上海互凌电气

一次电流 Primary current :	5A-5000A
二次电流 Secondary current I:	5A,1A
额定电压 Rated? voltage:	0.72KV
额定频率 Rated? frequency:	50-60Hz
额定负荷 Rated load:	1-30VA
准确级 Class :	0.5,1.0,3.0
额定安全系数 Rated security coefficient:	FS<5

技术参数 Technical parameter

型号 Type	额定电流 Rated current(A)	额定功率 Rated power(VA)	等级 Class	额定电压 Rated Voltage(V)	额定频率 Rated Frequency(Hz)
MR-28	30/5-100/5	1.5-5	0.5/1.0	720	50/60Hz
MR-42	100/5-250/5	5	0.5/1.0	720	50/60Hz
MR-45	300/5-400/5	5	0.5/1.0	720	50/60Hz
MR-60	400/5-800/5	5-10	0.5/1.0	720	50/60Hz
MR-85	600/5-1000/5	5-10	0.5/1.0	720	50/60Hz
MR-125	1200/5-5000/5	10-30	0.5/1.0	720	50/60Hz

安装尺寸 Dimension of case(mm)

型号 Type	ID	OD	HT
MR-28	28	70	40
MR-42	42	80	30
MR-45	45	80	30
MR-60	60	100	30
MR-85	85	120	20
MR-125	125	165	20