












## 技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1  
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 一次电流: 30~3000A, 二次电流: 1A、5A  
Primary Current: 30~3000A, Secondary Current: 1A、5A
- 额定频率50Hz或60Hz  
Rated Frequency: 50 or 60Hz
- 耐受电压: AC3kV(1min)  
Withstand Voltage: 3kV for 1min
- 环境温度: -25℃~45℃  
Environment Temperature: -25℃~45℃

| 产品型号<br>Product Model                                                                           | 电流比<br>Ratio(A) | 额定负荷 Burden(VA) |     |     |     | 穿心匝数<br>Cross-core<br>turn<br>number | 外形及安装尺寸<br>Outline and mounting dimensions(mm)                                        |
|-------------------------------------------------------------------------------------------------|-----------------|-----------------|-----|-----|-----|--------------------------------------|---------------------------------------------------------------------------------------|
|                                                                                                 |                 | Class:3.0       | 1.0 | 0.5 | 0.2 |                                      |                                                                                       |
| <br>OB-45/14   | 30/5            | 1               |     |     |     | 1                                    |    |
|                                                                                                 | 40/5            | 1               |     |     |     | 1                                    |                                                                                       |
|                                                                                                 | 50/5            |                 | 1.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 60/5            |                 | 2.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 75/5            |                 | 2.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 80/5            |                 | 2.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 100/5           |                 | 2.5 |     |     | 1                                    |                                                                                       |
| <br>OB-62/30 | 40/5            |                 | 1.5 |     |     | 1                                    |  |
|                                                                                                 | 50/5            |                 | 1.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 60/5            |                 | 1.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 75/5            |                 | 1.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 80/5            |                 | 1.5 |     |     | 1                                    |                                                                                       |
|                                                                                                 | 100/5           |                 |     | 2.5 |     | 1                                    |                                                                                       |
|                                                                                                 | 150/5           |                 |     | 2.5 |     | 1                                    |                                                                                       |
| <br>OB-62/40 | 200/5           |                 |     | 5   |     | 1                                    |  |
|                                                                                                 | 250/5           |                 |     | 5   |     | 1                                    |                                                                                       |
|                                                                                                 | 300/5           |                 |     | 5   |     | 1                                    |                                                                                       |
|                                                                                                 | 400/5           |                 |     | 5   |     | 1                                    |                                                                                       |
|                                                                                                 | 500/5           |                 |     | 5   |     | 1                                    |                                                                                       |
|                                                                                                 | 600/5           |                 |     | 7.5 |     | 1                                    |                                                                                       |
|                                                                                                 | 200/5           |                 | 5   |     |     | 1                                    |  |
| <br>OB-74/40 | 250/5           |                 | 5   |     |     | 1                                    |                                                                                       |
|                                                                                                 | 300/5           |                 | 5   |     |     | 1                                    |                                                                                       |
|                                                                                                 | 400/5           |                 | 5   |     |     | 1                                    |                                                                                       |
|                                                                                                 | 500/5           |                 |     | 10  |     | 1                                    |                                                                                       |
|                                                                                                 | 600/5           |                 |     | 10  |     | 1                                    |                                                                                       |
|                                                                                                 | 800/5           |                 |     | 10  | 5   | 1                                    |                                                                                       |



| 产品型号<br>Product Model                                                                             | 电流比<br>Ratio(A) | 额定负荷 Burden(VA) |     |     |     | 穿心匝数<br>Cross-core<br>turn<br>number | 外形及安装尺寸<br>Outline and mounting dimensions(mm)                                        |
|---------------------------------------------------------------------------------------------------|-----------------|-----------------|-----|-----|-----|--------------------------------------|---------------------------------------------------------------------------------------|
|                                                                                                   |                 | Class:3.0       | 1.0 | 0.5 | 0.2 |                                      |                                                                                       |
| <br>OB-74/50     | 300/5           |                 |     | 5   |     | 1                                    |    |
|                                                                                                   | 400/5           |                 |     | 5   |     | 1                                    |                                                                                       |
|                                                                                                   | 500/5           |                 |     | 10  |     | 1                                    |                                                                                       |
|                                                                                                   | 600/5           |                 |     | 10  |     | 1                                    |                                                                                       |
|                                                                                                   | 800/5           |                 |     | 10  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1000/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
| <br>OB-86/60     | 500/5           |                 |     | 10  |     | 1                                    |    |
|                                                                                                   | 600/5           |                 |     | 10  |     | 1                                    |                                                                                       |
|                                                                                                   | 800/5           |                 |     | 10  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1000/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1200/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1500/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
| <br>OB-104/80  | 800/5           |                 |     | 15  | 5   | 1                                    |  |
|                                                                                                   | 1000/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1200/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1500/5          |                 |     | 15  | 10  | 1                                    |                                                                                       |
|                                                                                                   | 1600/5          |                 |     | 15  | 10  | 1                                    |                                                                                       |
|                                                                                                   | 2000/5          |                 |     | 20  | 10  | 1                                    |                                                                                       |
| <br>OB-140/100 | 800/5           |                 |     | 15  | 5   | 1                                    |  |
|                                                                                                   | 1000/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1200/5          |                 |     | 15  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1500/5          |                 |     | 20  | 5   | 1                                    |                                                                                       |
|                                                                                                   | 1600/5          |                 |     | 20  | 10  | 1                                    |                                                                                       |
|                                                                                                   | 2000/5          |                 |     | 20  | 15  | 1                                    |                                                                                       |
| <br>OB-150/100 | 2500/5          |                 |     | 20  | 15  | 1                                    |  |
|                                                                                                   | 1500/5          |                 |     | 15  | 15  | 1                                    |                                                                                       |
|                                                                                                   | 1600/5          |                 |     | 15  | 15  | 1                                    |                                                                                       |
|                                                                                                   | 2000/5          |                 |     | 15  | 15  | 1                                    |                                                                                       |
|                                                                                                   | 2500/5          |                 |     | 15  | 15  | 1                                    |                                                                                       |
|                                                                                                   | 3000/5          |                 |     | 20  | 20  | 1                                    |                                                                                       |
|                                                                                                   | 3200/5          |                 |     | 20  | 20  | 1                                    |                                                                                       |

\*长期使用100%额定一次电流，订货需特殊说明。

\*If it carries 100% rated primary current for long term, please indicate this point when to book the product.