



保护级电流互感器 Type wound ring type (measuring current transformers)

技术参数 Technical data

型号 Type	等级 Class				10						10P10					10P15			
	RATIO	ID	OD	VA	5	7.5	10	15	20	30	5	7.5	10	15	20	5	7.5	10	15
PR1	100/5	30	95	厚度 mm	50	60	75	100	130	-	85	100	-	-	-	-	-	-	-
	120/5	30	95		50	60	70	95	120	-	80	105	-	-	-	-	-	-	-
	150/5	30	95		40	50	60	80	110	-	65	90	110	-	-	-	-	-	-
	200/5	28	95		40	40	40	55	65	-	60	6	70	-	-	-	-	-	-
PR2	150/5	40	100	厚度 mm	50	55	65	85	100	-	75	100	110	120	-	-	-	-	-
	200/5	40	100		40	40	50	60	70	-	55	70	85	110	-	-	-	-	-
	250/5	40	95		40	40	50	60	70	-	50	70	85	110	-	75	95	-	-
	300/5	40	95		35	40	40	60	65	85	50	60	70	95	-	70	85	105	-
PR3	200/5	45	95	厚度 mm	40	55	60	80	100	115	75	95	110	-	-	-	-	-	-
	250/5	45	95		40	50	60	70	85	110	60	75	90	115	-	85	110	-	-
	300/5	45	95		35	40	40	60	70	95	50	65	80	100	-	70	90	-	-
	400/5	45	95		35	40	40	60	60	85	50	55	65	85	-	65	80	95	-
PR4	400/5	58	100	厚度 mm	35	40	40	60	70	90	60	65	80	100	-	75	95	110	-
	550/5	58	100		35	40	40	60	60	80	50	60	70	85	110	70	80	95	-
	600/5	57	100		35	35	40	50	60	70	50	50	60	80	90	60	75	85	110
	800/5	55	104		35	35	35	40	50	60	40	50	50	60	80	55	65	75	90
PR5	600/5	70	114	厚度 mm	35	35	40	50	50	70	50	55	60	80	95	70	80	90	110
	800/5	70	114		35	35	35	40	40	55	40	40	50	60	70	50	60	70	85
	1000/5	68	116		35	35	35	35	40	50	35	40	50	55	65	50	55	65	80
	1200/5	67	117		35	35	35	35	35	40	35	40	40	50	60	40	50	55	65
PR6	800/5	85	125	厚度 mm	35	35	35	40	50	60	40	50	55	65	80	60	65	75	95
	1000/5	83	127		35	35	40	40	40	60	40	40	50	60	75	50	60	70	85
	1200/5	83	128		35	35	35	35	40	40	35	35	40	45	60	40	50	60	65
	1600/5	82	130		35	35	35	35	35	40	35	35	35	40	50	40	50	50	65
PR7	1200/5	110	152	厚度 mm	35	35	35	35	40	50	40	40	50	45	65	50	60	65	80
	1600/5	110	155		35	35	35	35	35	40	35	35	35	40	50	35	50	50	60
	2000/5	108	158		30	30	30	30	30	30	35	35	35	40	35	40	50	50	
	2500/5	106	162		30	30	30	30	30	30	35	35	35	35	40	35	35	40	50
PR8	1600/5	120	165	厚度 mm	30	30	30	35	35	40	35	40	40	45	60	50	50	55	65
	2000/5	120	165		30	30	30	35	35	40	35	35	40	40	50	40	40	50	55
	2500/5	118	168		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
	3000/5	116	170		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
PR9	2000/5	130	175	厚度 mm	30	30	30	35	35	40	35	35	40	40	50	40	50	50	60
	2500/5	130	175		30	30	30	35	35	40	35	35	35	40	40	35	40	40	50
	3000/5	128	178		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
	3500/5	126	180		30	30	30	35	35	35	35	35	35	40	40	35	35	40	40
PR10	2500/5	140	185	厚度 mm	35	35	35	35	40	40	35	35	40	40	50	35	40	50	60
	3000/5	140	185		35	35	35	35	35	40	35	35	35	40	40	35	40	40	50
	3500/5	138	188		35	35	35	35	35	35	35	35	35	40	40	35	35	40	40
	4000/5	136	190		35	35	35	35	35	35	35	35	35	40	40	35	35	40	40

