






技术参数 Technical data

- 产品性能符合标准 GB1208和IEC60044-1
The current transformers are in accordance with GB1208 and IEC60044-1 standards
- 额定电压: 0.66kV
Rated voltage 0.66kV
- 额定频率50Hz或60Hz
Rated frequency 50Hz or 60Hz
- 额定二次电流: 5A或1A
Rated secondary current 5A or 1A
- 环境温度: -5℃~+40℃
Ambient temperature -5℃~+40℃

主要技术参数及外形安装尺寸 The main technical parameters and dimensions

产品型号 Product Model	电流比 Ratio(A)	额定负荷 Burden(VA) Class:0.5 1.0		穿心匝数 Cross-core turn number	外形及安装尺寸 Outline and mounting dimensions(mm)
 RCT-25	75/5	2.5	2.5	1	
	100/5	2.5	2.5	1	
 RCT-35	75/5	2.5	2.5	1	
	100/5	2.5	2.5	1	
	150/5	5	5	1	
	200/5	5	5	1	
	250/5	5	5	1	
	300/5	5	5	1	
 RCT-60	400/5	5	5	1	
	500/5	10	10	1	
	600/5	10	10	1	
	750/5	10	10	1	
	800/5	10	10	1	
	1000/5	10	10	1	
	1200/5	10	10	1	

产品型号 Product Model	电流比 Ratio(A)	额定负荷 Burden(VA)		穿心匝数 Cross-core turn number	外形及安装尺寸 Outline and mounting dimensions(mm)
		Class:0.5	1.0		
 RCT-90	800/5	10	10	1	
	1000/5	10	10	1	
	1200/5	10	10	1	
	1500/5	10	10	1	
	1600/5	10	10	1	
 RCT-110	1500/5	10	10	1	
	1600/5	10	10	1	
	2000/5	20	20	1	
	2500/5	20	20	1	
	3000/5	20	20	1	

订货须知 Ordering Instructions

用户在订货时，需提供以下信息：

- 产品型号及穿心孔直径
- 电流比
- 额定输出及相应准确级

例如：订货RCT型，穿心孔直径为60mm、电流比800/5A、额定输出10VA、准确级0.5级的互感器。

订货代号为：RCT-60 800/5A 10VA 0.5级。

- 如有特殊要求时，可与厂家协商定制。

When the customer ordering, need to provide the following information:

- product type and diameter of center hole
- The current ratio
- rated output and the corresponding accuracy class

For example: order RCT type, the center hole diameter is 60mm, 800/5A, 10VA rated output current ratio, accuracy class 0.5 transformer.

Ordering code named: RCT-60 800/5A 10VA 0.5.

- if there are special requirements, can consult with the manufacturers custom.