

### ◆ 技术参数与规格

一次电流: 100A-5000A  
 二次电流: 5A, 1A  
 标准: BS7626, IEC44-1  
 最大电压: 0.72KV  
 频率: 50-60Hz  
 额定负载: 2.5VA-60VA  
 精度: 0.5, 1.0, 3.0  
 短时热电流:  $I_{th}=100 I_h$   
 额定安全系数:  $F_s < 5$   
 高阻燃性和安全性  
 可以适用于不同的安装尺寸

Primary current: 100A - 500A  
 Secondary approval: 5A, 1A  
 Standard current: BS7626, IEC60044-1  
 Maximum voltage: 0.72KV  
 Frequency: 50 - 60Hz  
 Rated load: 2.5VA - 60VA  
 Class: 0.5, 1.0, 3.0  
 Short-time thermal current:  $I_{th}=100 \times I_h$   
 Rated security coefficient:  $F_s < 5$   
 -High fire retardancy and security  
 -Wide range of sizes to accommodate all the existing installations



型号Model	额定电流(A)一次/二次 Rated current(A)Primary/Secondary
SDH-40	100/5, 150/5, 200/5, 250/5, 300/5, 400/5, 500/5, 600/5A
SDH-60	300/5, 400/5, 500/5, 600/5, 750/5, 800/5, 1000/5, 1200/5A
SDH-80	500/5, 600/5, 750/5, 800/5, 1000/5, 1200/5, 1500/5, 1600/5A
SDH-100	600/5, 750/5, 800/5, 1000/5, 1200/5, 1500/5, 1600/5, 2000/5A, 2500/5, 3000/5A
SDH-120	1000/5, 1200/5, 1500/5, 1600/5, 2000/5, 2500/5, 3000/5, 4000/5A, 5000/5

### ◆ 尺寸 Dimension

型号Model	尺寸 Dimension			窗口尺寸 Window way Dimension		安装尺寸 Install Dimension
	W	H	D	A	E	M
SDH-40	75	105	45	42	32	45
SDH-60	98	116	45	62	32	42
SDH-80	118	120	45	82	32	60
SDH-100	140	130	49	102	32	80
SDH-120	165	152	49	102	53	80

### ◆ 外形及安装尺寸 Overall dimension drawing

